

# SITING LED TRAFFIC SIGNS

## THE EDGE DISTANCE,

THE DISTANCE BETWEEN THE EDGE OF THE CARRIAGEWAY AND THE EDGE OF THE SIGN FACE NEAREST THE CARRIAGEWAY SHOULD **NOT BE LESS THAN 0.75M**



## THE MOUNTING HEIGHT,

THE HEIGHT OF THE LOWEST EDGE OF THE SIGN ABOVE THE VERGE/FOOTWAY **SHOULD NOT BE LESS THAN 2.15M**



THE SIGN SHOULD NOT BE VISUALLY INTRUSIVE FROM **WINDOWS OF ADJOINING PROPERTIES**



THE SIGN SHOULD BE SITED SO AS NOT OBSTRUCT VISIBILITY FROM **SIDE ROADS / ACCESSES.**



CARE SHOULD BE TAKEN IF SITING ON THE INSIDE OF A BEND, SO THAT FORWARD VISIBILITY AROUND THE BEND **IS NOT OBSTRUCTED.**

CARE SHOULD BE TAKEN TO AVOID **UNNECESSARY VISUAL INTRUSION** INTO THE GENERAL LANDSCAPE.



IT IS PREFERABLE **NOT** TO SITE A SIGN UNDER AN OVERHANGING **TREE/HEDGE.**



THERE MUST BE **NO CONFLICT** WITH OTHER SIGNS WITHIN THE IMMEDIATE VICINITY.

Existing signs should not be obscured.

THE SIGN SHOULD NOT OVERHANG AN EXISTING HIGHWAY BOUNDARY WITHOUT THE **ADJOINING OWNERS' CONSENT.**

THE SIGN MUST BE **CLEARLY VISIBLE** TO APPROACHING TRAFFIC.



SIGNS SHALL **NOT REPLACE** PERMANENT SIGNAGE (REGULATORY AND IN CASE OF POWER FAILURE)



ALL LED SIGNS SHOULD BE COMPLIANT WITH NATIONAL TRAFFIC SIGNS REGULATIONS AND GENERAL DIRECTIONS (TSRGD 2002)

Contact Messagemaker Displays today on 01737 774747 or Email: [sales@messagemaker.co.uk](mailto:sales@messagemaker.co.uk)