

FIXED VMS DISPLAY



POST OR WALL-MOUNTED
FIXED VARIABLE MESSAGE
SIGN WITH FULL COLOUR
SCREEN EASILY UPDATED
AND MONITORED FROM
REMOTE LOCATIONS

KEY FEATURES

- ▶ Full colour display
- ▶ Weatherproof casing designed for outdoor use
- ▶ 4G, Bluetooth and Ethernet connectivity available
- ▶ Energy efficient LED technology



COMPATIBLE WITH RCS

- ▶ Real-time updates from remote locations
- ▶ Status monitoring
- ▶ Easy-to-use message scheduling and changing

	DIA16	DIA20
Standard	EN12966	EN12966
Display Size (h x w)	640 x 768 mm	640 x 640 mm
Pitch Size	16 mm	20 mm
Screen Resolution (h x w)	40 x 48 pixels	32 x 32 pixels
LED Type	3-in-1 SMD	3-in-1 SMD
Display Colour	Full Colour	Full Colour
Display Content Ability	Max 5 Lines of 6 Characters or 1 x 600 mm Traffic Symbol	Max 4 Lines of 5 Characters or 1 x Traffic Circle
Interface	RS232 / RS485 / Ethernet / 4G	RS232 / RS485 / Ethernet / 4G
Housing Material	Aluminium (Black)	Aluminium (Black)
Maintenance Access	Front of screen	Front of screen
IP Rating	IP65	IP65
Optional Extra	Vehicle Detection Radar	Vehicle Detection Radar